



## **AeroPro Leisure 165N Auto**

Reference# 83136-10990

## AeroPro Leisure 165N Lifejacket

SeaLion Leisure is an inflatable lifejacket, with a UML automatic inflator, and is primarily intended for the leisure craft market, but may also be used in work situations where at least 150N buoyancy is required. The Norwegian Society for Sea Rescue (NSSR) supplies a similar lifejacket to the domestic market. The standard model comes with quick drying fleece around the neck, back support and crotch straps for increased comfort and safety. Certified in accordance with ISO 12402-3.

## **Facts**

- AeroPro Leisure 165N is a single-chamber lifejacket
- AeroPro 165N is an inflatable lifejacket with automatic UML-inflator with 33g CO<sub>2</sub> cylinder
- · Standard model is delivered with soft fleece in neck for comfort
- The lifejacket is padded with spacer mesh on the part towards the body for comfort
- · Crotch strap for safety
- Complete back piece (also padded) for better distribution of load
- · High quality lifejacket, made in EU
- Inflated bladder provides minimum 165N buoyancy
- Cover in black Condura

Product Detail	
Lifejacket	Lifejacket work
Type of PFD/class	Inflatable lifejacket 150N
Area of application	Multi-purpose
Buoyancy	Minimum 165N
Material	Polyester
Adjustments	Crotch strap maximum circumference 140 cm Waist belt max 140 cm - min 55 cm
Fit / Ergonomics	Ergonomic
Colour	990 Black
Reflective material	IMO Solas
Pockets	Yes
Bladder construction	Symmetrical
Inflator mechanism/operating head	Water activated, standard UML Pro Sensor
Whistle	Yes
Inspection window for inflator	Yes
Upholstery/Padding	Soft fleece in neck Spacermesh
Buckle	Plastic buckle with quick release functionality
Cover closure	Zipper with Quick Burst functionality
Compatibility	Yes, ISO with ISO suit
CO2-cylinder(s)	33g CO <sub>2</sub> (1pc)
Service interval (standard)	1 year (professional use) 2 year (leisure)
Certifications ISO	ISO 12402-3 Lifejackets for offshore conditions (150N)
Crotch strap	Single

## **Certificates**

ISO 12402-3

