



SeaLion SOLAS 150N

Reference# 82912-05990STD

SeaLion 150N Solas Lifejacket

Our collection of SeaLion Solas lifejackets is designed for users with high demands on function and comfort. This lifejacket can be used in combination with our immersion suits. The SeaLion Solas provides minimum 150N buoyancy and is certified in accordance with SOLAS' LSA Code. SeaLion lifejackets are designed to inflate automatically when they come in contact with water and contribute to the turning the body face up in the sea.

Facts

- Lightweight and comfortable, construction with focus on comfort
- Contoured around head and neck
- Rough, durable cover fabric in black nylon
- Easy operated front buckle in stainless steel
- Adjustment of waist webbing in the side
- HalkeyRoberts inflators - water activated (automatic)
- Retro reflective tape (SOLAS)
- Whistle, lifting loop, emergency light and buddy line
- Double buoyancy bladder in high-vis material
- Interlocking, assymetrical bladder prevents water to be channelled to your airways (Wave Barrier Technology)

Product Detail

Lifejacket	<i>For shipping & offshore</i>
Type of PFD/class	<i>Inflatable lifejacket 150N Solas</i>
Area of application	<i>Multi-purpose Shipping</i>
Buoyancy	<i>Minimum 150N</i>
Material	<i>Polyester</i>
Adjustments	<i>Waist belt extender available, up to 180 cm Waist belt max 140 cm - min 50 cm</i>
Fit / Ergonomics	<i>Ergonomic Long</i>
Colour	<i>990 Black</i>
Reflective material	<i>IMO Solas</i>
Bladder construction	<i>Asymmetrical</i>
Inflator mechanism/operating head	<i>Water activated, Halkey Roberts (2 pcs)</i>
Buddy line	<i>Yes</i>
Whistle	<i>Yes</i>
Emergency light	<i>IMO Solas, water activated</i>
Buckle	<i>Stainless steel buckle</i>
Cover closure	<i>Velcro</i>
Compatibility	<i>Yes, IMO with IMO suit</i>
CO₂-cylinder(s)	<i>33g CO₂ (2 pcs)</i>
Service interval (standard)	<i>1 year</i>
Certifications SOLAS lifejacket	<i>150N</i>

Certificates

SOLAS 150N

Contact us

Hansen Protection AS, PB. 218, N-1501 Moss
Tel. +47 69 00 13 00, e-post: hpro@hansenprotection.no