



SeaLion Alu FR ISO 150N

Reference# 83118-99930STD

SeaLion Alu FR lifejackets are designed for users with high demands on function and comfort. The lifejacket is ISO Approved and specially designed for environments with high temperatures. The lifejacket cover is made of material which is inherently flame retardant and heat reflective. The lifejackets will inflate automatically in contact with water and contribute to the turning of the body face up also when wearing a suit. SeaLion lifejackets are designed as combined working / abandonment lifejackets. Certified in accordance with ISO 12402-3.

Facts

- Lightweight and comfortable, construction with focus on comfort
- Contoured around head and neck + soft neoprene in neck
- Rough, durable cover fabric in flame retardant and heat reflective material
- Easy operated front buckle in plastic
- Adjustment of waist webbing in the side
- Hammar inflator - water activated (automatic)
- Retro reflective tape (SOLAS)
- Whistle, lifting loop and emergency light
- Crotch strap
- Double buoyancy bladder in high-vis material
- Service friendly - buoyancy bladder may easily be detached from cover

Product Detail

Lifejacket	<i>Lifejacket work</i>
Type of PFD/class	<i>Inflatable lifejacket 150N</i>
Area of application	<i>Shipping</i>
Buoyancy	<i>Minimum 150N</i>
Material	<i>Flame retardant Heat reflective</i>
Adjustments	<i>Crotch Strap Waist belt max 140 cm - min 50 cm</i>
Fit / Ergonomics	<i>Ergonomic Long</i>
Colour	<i>Silver</i>
Reflective material	<i>IMO Solas</i>
Bladder construction	<i>Symmetrical</i>
Inflator mechanism/operating head	<i>Hydrostatic sensor, Hammar</i>
Whistle	<i>Yes</i>
Emergency light	<i>IMO Solas, water activated</i>
Buckle	<i>Plastic buckle with quick release functionality</i>
Cover closure	<i>Velcro</i>
Compatibility	<i>Yes, ISO with ISO suit</i>
CO₂-cylinder(s)	<i>33g CO₂ (1pc)</i>
Service interval (standard)	<i>1 year (professional use) 2 year (leisure)</i>
Certifications ISO	<i>ISO 12402-3 Lifejackets for offshore conditions (150N)</i>
Crotch strap	<i>Single</i>

Certificates

ISO 12402-3

Contact us

Hansen Protection AS, PB. 218, N-1501 Moss

Tel. +47 69 00 13 00, e-post: hpro@hansenprotection.no