



SeaMob AES

Reference# 82650-55290L

SeaMob AES

A suit specifically designed for rescue personnel on evacuation of ships and for use in MOB boats. SeaMOB is manufactured in 3 mm flame retardant, waterproof neoprene that provides insulation and buoyancy and is certified for use without lifejacket. The suit has an integrated, manual inflatable lung for proper flow position and increased freeboard. Fixed neoprene boots on the suit can be used in combination with fins.

Facts

- Suit material in flame retardant neoprene with inherent insulation and buoyancy
- Ergonomic construction and elastic suit material provides comfort in use
- Waterproof zip in soft PU/plastic; easy to handle
- · Solas approved reflective patches
- · Reinforcements in extremely durable laminated PU on elbows, knees and seat
- Lifting strap with D-ring and carbine hook
- · Integrated manually inflatable buoyancy lung for floating position and free-board
- Boots may be used with flippers
- Buddy line with floating hook, whistle and emergency light
- Neoprene gloves and double neoprene cuffs
- · Leg tightening zips to adjust fitting
- Approved for use without lifejacket
- SOLAS approved and in accordance with the LSA-code MED 1.6a as an immersion suit and Anti Exposure Suit (AES)

Product Detail	
Area of application	Multi-purpose
Type of suit	Work suit
Material	Neoprene 3mm
Adjustments	Leg thighteners with zipper for good fit
Main zipper type	Soft PU/plastic with teeth, open
Wrist seals	Neoprene
Colour	Orange
Reflective material	IMO Solas
Pockets	Radio pocket on chest Sleeve pockets
Hood	Integral, in suit material
Gloves	3-finger neoprene (detachable)
Lifting becket/loop	Yes, with D-ring and carbine hook in stainless steel
Inflation valve for buoyancy	Manual inflation valve for extra bladder in collar
Buddy line	Yes, with floating buddy hook in shoulder pocket
Whistle	Yes, easy accessible in zipper slider
Emergency light	IMO Solas, water activated
ID tag	Yes, pocket
Boots / socks	PVC boots - may be used with swim fins
Reinforcement knee	Laminated layer of PU-reinforcement material
Reinforcement in seat	Laminated layer of PU-reinforcement material
Compatibility	May be used without lifejacket
Thermal protection with lining/inherent insulation	1 hour (IMO/Solas less than 5°C watertemp)
Thermal protection without lining/inherent insulation	1 hour (IMO/Solas less than 5°C watertemp)
Service interval (standard)	3 year
Certifications SOLAS-suit (w/integral buoyancy)	Solas MED/1.6a (un-insulated - worn without lifejacket) Solas MED/1.6c (anti exposure suit without lifejacket)

Certificates

SOLAS

